

GRAY DUCT TAPE FOR GENERAL PURPOSE

PRODUCT DESCRIPTION

Hot melt adhesive tape with polyethylene backing reinforced with polyester fibers. Characterized by excellent conformability, it adheres to various types of surfaces and can be tear by hand. Suitable for protection and sealing operations in daily repairs and DIY activities in multiple contexts such as the home, construction sites and industrial interventions. Also used for joining objects and reinforcing packaging.



FEATURES



Noisy unwinding



Hand tearable



Super adhesive



Water resistant

MAIN APPLICATIONS



Temporary repairs/DIY



Bundling/ reinforcement

BACKING MATERIAL

POLYETHYLENE REINFORCED WITH POLYESTER FIBERS, GRAY OUTSIDE, WHITE INSIDE

AVAILABLE VERSIONS

J = jumbo

COLOURS



TYPE OF ADHESIVE

HOT MELT

TECHNICAL DATA	Metric	Value	Test Method
Backing thickness	µm	55	AFERA 5006
Total thickness	µm	165	AFERA 5006
Adhesion to steel	N/cm	7	AFERA 5001
Tensile strength	N/cm	30	AFERA 5004
Elongation at break	%	12	AFERA 5004

Technical Informations, storage and product use

The product must be used within 12 months from the delivery date (6 months if jumbo). It is advisable to keep the material in its original packaging, away from heat sources and away from direct light. The storage temperature must be between 15° and 30° C and the relative humidity between 40 and 60%. For storage temperatures other than those indicated, recondition the product to the levels described above. The technical data shown in the data sheets are the average of the analyzes obtained on normal production. Aging can determine the variation of some technical and aesthetic characteristics of the product within the time limits indicated above without affecting its quality and functionality. The technical data shown are reported with a tolerance of +/- 10% and may be modified at any time for production needs or technical updates.

Fabo spa declines all responsibility for direct damage and for the consequences deriving from improper use of the product. It is advisable to check the conformity of the product in relation to the specific conditions of use.

Rev.02_15/01/2024